

PV-male and female cable coupler MC4



TECHNICAL DATA

With Snap-in lock

Temperature range	-40°C to +90°C
Protection class	IP 67
Safety class	II
Rated voltage	1000 V (IEC)

Rated current	22A (2.5 mm ²), 30A (4mm ² , 6mm ²)
Contact resistance	0.35 mOhm

■ STRUCTURE

- Material: Polyamide (PA)
- Contact: Cu, tinned, rotated

MC4 male cable coupler

Part no.	cross-section from / to mm ²	Cable Ø from / to mm	Packaging unit (in pc.)
905206	2.5	3.0 - 6.0	50
905208	2.5	5.5 - 9.0	50
905210	4.0 - 6.0	3.0 - 6.0	50

Part no.	cross-section from / to mm ²	Cable Ø from / to mm	Packaging unit (in pc.)
904963	4.0 - 6.0	5.5 - 9.0	50
905863	10.0	5.5 - 9.0	50

MC4 female cable coupler

Part no.	cross-section from / to mm ²	Cable Ø from / to mm	Packaging unit (in pc.)
905207	2.5	3.0 - 6.0	50
905209	2.5	5.5 - 9.0	50
905211	4.0 - 6.0	3.0 - 6.0	50

Part no.	cross-section from / to mm ²	Cable Ø from / to mm	Packaging unit (in pc.)
904964	4.0 - 6.0	5.5 - 9.0	50
905864	10.0	5.5 - 9.0	50